

Product Environmental Profile **Trus Joist® I-Joist®**

We use environmentally sound practices and our products are sourced from responsibly managed forests

ANNUAL DATA FOR 2015

PRODUCT

Name/description: Trus Joist® I-joist
 Mill locations: Eugene, OR; Evergreen, AL; Natchitoches, LA

FIBER SOURCING

Category ⁽¹⁾	Amount
Certified ⁽²⁾	N/A
Responsible ⁽³⁾	100%
Non-controversial ⁽⁴⁾	100%
Country of harvest	United States & Canada
Certifications	See reverse

PRODUCT COMPOSITION


Wood Fiber	>91%
Other	Resin, co-binder, wax; no added urea formaldehyde resins

SPECIES

United States (flange)


Douglas-fir	<i>Psuedotsuga menziesii</i>	Soft maple	<i>Acer rubrum</i>
Loblolly pine	<i>Pinus taeda</i>	Sweet gum	<i>Liquidambar styraciflua</i>
Longleaf pine	<i>Pinus palustris</i>	White pine	<i>Pinus strobes</i>
Longleaf pine	<i>Pinus palustris</i>	Yellow	<i>Liriodendron</i>
Slash pine	<i>Pinus elliotii</i>		
Spruce pine	<i>Pinus glabra</i>	Canada (web)	
Western hemlock	<i>Tsuga heterophylla</i>	Aspen	<i>Populus</i>
United States (web)		Birch	<i>Betula lenta</i>
Aspen	<i>Populus tremuloides</i>	Black	<i>Populus nigra</i>
Basswood	<i>Tilia Americana</i>	Engelmann spruce	<i>Picea engelmanni</i>
Hard maple	<i>Acer saccharum</i>	Lodgepole	<i>Pinus contorta</i>
Jack pine	<i>Pinus banksiana</i>	White	<i>Picea glauca</i>
Loblolly pine	<i>Pinus taeda</i>		
Longleaf pine	<i>Pinus Palustris</i>		
Red pine	<i>Pinus resinosa</i>		
Shortleaf pine	<i>Pinus echinata</i>		

CARBON FOOTPRINT



ENERGY USED IN MANUFACTURING


Fossil fuel
 Purchased electricity



RESIDUALS MANAGEMENT

Remaining material from manufacturing process

Burned for energy
 Beneficially reused (e.g., land applied or recycled)
 Landfilled
 Incinerated or disposed in permitted hazardous waste facilities (<1%)




AIR

Compound	kg/admt
Carbon monoxide (CO)	0.03
Nitrogen oxides (NOx)	0.04
Particulate matter (PM)	0.39
Sulfur dioxide (SO ₂)	0.0002
Volatile organic compounds (VOC)	0.35

WATER

Water used in the production of products is generally reused in the process or discharged into an approved water treatment facility. Storm water at these facilities is managed according to all federal, state and local regulations.



SUSTAINABLE FORESTRY

We manage forests for both wood production and the ecosystem services they provide. These include clean water, habitat for fish and wildlife, and sites of cultural, historic and scenic importance. We implement landscape-level forest management as part of our compliance with the Sustainable Forestry Initiative® (SFI) standard. Over the past five years, we have planted more than 670 million tree seedlings.

CERTIFICATION AND PRODUCT LABELING

Nearly all of our manufacturing facilities and forests have environmental management systems that align with the ISO 14001 standard. All of our forests are certified to sustainable forestry standards. And, nearly all of our North American-made forest products are eligible to use a sustainable forestry label.

	<u>Certification #</u>	<u>Expiration Date</u>
Natchitoches and Eugene SFI Fiber Sourcing	4Z531-SP5	9/14/2017

ABOUT TJI JOIST

Trus Joist® developed the wooden I-joist over 45 years ago and revolutionized the world of floor framing. Engineered to provide strength and consistency, these joists are a key part of making a high-performance floor. The dimensional stability of TJI® joists helps them resist warping, twisting, and shrinking that can lead to squeaky floors. TJI® joists are lightweight and come in long lengths. This helps save on labor because they are faster and easier to install than traditional framing.

- (1) Per ASTM D7612-10 Standard Practice for Categorizing Wood and Wood-Based Products According to Their Fiber Sources.
- (2) Average certified content for wood purchased by all facilities. Verification: selected facilities certified to the SFI & PEFC Chain of Custody standards.
- (3) Verification: all Weyerhaeuser manufacturing facilities certified to the SFI Certified Sourcing Standard.
- (4) All forest-based raw material sourced in North America. Verification: selected facilities certified to the SFI, PEFC & FSC Chain of Custody Standards and FSC Controlled Wood Standard.
Carbon dioxide equivalent (CO₂e) is the standard metric used to compare emissions from various GHGs based on their global warming potential. For example, the global warming potential for methane is 25, so 1 ton of methane emissions is equivalent to 25 tons of carbon dioxide (25 CO₂e). Greenhouse gases (GHG) include carbon dioxide, methane, nitrous oxide, HFCs, PFCs and SF6. Kilogram (kg).
- (5) Air Dried Metric Ton (admt).
- (6) Direct emissions (Scope 1) are from sources owned or controlled by Weyerhaeuser.
- (7) Additives include the GHG emissions associated with the manufacturing of resins and wax used in this product. These emissions are estimated from an industry standard.
- (8) Product sequestration is the amount of carbon (shown as equivalent amount of CO₂) that remains in the finished product for 100 years. This calculation is done using the ICFPA/NCASI Tools for Calculating Biomass Carbon Stored in Forest Products in-Use, Version 1.0A.

PROCUREMENT SYSTEM CERTIFICATION

All of our mills are independently certified as meeting the procurement provisions of the SFI Certified Sourcing standard. This means:

- We know the areas and types of suppliers our wood comes from.
- We do not knowingly purchase wood, wood fiber, or products for distribution that originate from illegal logging.
- We use independent auditors.
- We reach out to and educate family forest owners about sustainable forestry.

CLIMATE CHANGE

We are committed to reducing our greenhouse gas emissions and limiting our use of fossil fuels by using carbon-neutral biomass for our energy needs. Our goal is to reduce our greenhouse gas emissions 40 percent by 2020, compared with 2000 levels. By the end of 2015, our total (or absolute) greenhouse gas emissions decreased by 29 percent from 2000.

RESIDUALS MANAGEMENT

We use an average of 98 percent of each log in our manufacturing processes. Once our lumber is milled, the residuals of the milling process are used to make additional products (such as pulp, paper, or OSB) or to generate energy for our facilities.

ENERGY USE

Company-wide, we meet 80 percent of our energy needs by using renewable and carbon-neutral biomass fuels such as bark, wood residuals and other organic byproducts of our manufacturing process. Increasing the use of renewable biomass-based fuels reduces the use of fossil fuels and associated carbon dioxide emissions.

LEARN MORE...

- <http://wy.com/sustainability/environment/product-stewardship/safety-data-sheets/>
- ICC-ES Report
www.woodbywy.com/document/var-1008/